



MERU UNIVERSITY OF SCIENCE AND TECHNOLOGY
P.O. Box 972-60200 – Meru-Kenya
Tel: +254(0) 799 529 958, +254(0) 799 529 959, + 254 (0) 712 524 293,
Website: info@must.ac.ke Email: info@must.ac.ke

University Examinations 2023/2024

**SECOND YEAR SECOND SEMESTER EXAMINATION FOR THE DEGREE OF
BACHELOR OF SCIENCE COMPUTER SCIENCE AND BACHELOR OF COMPUTER
SECURITY AND FORENSICS**

CCS 3252: ASSEMBLY LANGUAGE PROGRAMMING

DATE: APRIL 2024

TIME: 2 HOURS

INSTRUCTIONS: *Answer question **one** and any other **two** questions*

QUESTION ONE (30 MARKS)

- a) Discuss the role of registers in assembly language programming. What are the advantages of using registers? (4 marks)
- b) Use an example to describe the basic structure of an assembly language instruction. (4 marks)
- c) Describe the purpose of the following. (6 marks)
 - i) ORG 100h
 - ii) DUP
 - iii) EQU
- d) Differentiate between ARM and MIPS architectures. (2 marks)
- e) Describe the purpose of the following general-purpose registers. (6 marks)



MUST is ISO 9001:2015 and



ISO/IEC 27001:2013 CERTIFIED

- i. Base register (BX)
- ii. Stack Pointer register (SP)
- iii. Destination Index register (DI)

f) Describe the stack data structure and explain how it is used in assembly language programming. (4 marks)

g) Write an assembly language to multiply 2 different values stored in different registers and store result into a register. (4 marks)

QUESTION TWO (20 MARKS)

a) Briefly illustrate the purpose of each line in the program below indicating the result of each register involved. (6 marks)

Mov ax,6

Mov bx,4

Cmp ax,bx

Jz L2

Mov cx,5

L2:

Mov cx,7

b) Use examples to illustrate the following as used in assembly language. (4 marks)

a) AND logical operator

b) OR logical operator

c) Write an Assembly to divide 9 by 2 and indicated the affected registers. (6 marks)



- d) Compute the physical address computed by the processor in displacement addressing mode when DS =100, BX 40, SI = 50 and displacement =35. (4 marks)

QUESTION THREE (20 MARKS)

- a) What are the contents of eax, ebx and ecx registers after the code fragment below is executed. (4 marks)

section .data

x: dd 54

y: dd 78

section .text

```
mov  eax,  x
```

```
mov  ebx, [eax]
```

```
add  ecx,  ebx
```

```
mov  eax, [eax]
```

- b) Write an assembly language program to move 12 bytes of string data from the source segment 4000H and source index 2000H to destination segment 80001-1 and destination index 6000H (6 marks)
- c) Convert the following to hexadecimal. (6 marks)

i. 672

ii. 426

- d) Use examples to differentiate between JMP and LOOP. (4 marks)

QUESTION FOUR (20 MARKS)

- a) Registers have developed from 8-bit to 64-bit processors. Discuss the progression based on general purpose registers. (6 marks)
- b) Write an assembly to add 2 numbers using a function/procedure and return the result. (6 marks)



MUST is ISO 9001:2015 and



ISO/IEC 27001:2013 CERTIFIED

- c) Differentiate between data segment and stack segment registers. (4 marks)
- d) Write a program to make use of CMP to compare 2 values and give the bigger and the smaller value. Indicate the flags that will be affected (6 marks)

QUESTION FIVE (20 MARKS)

- a) Write the meaning of each of lines in the program below. (6 marks)

```
MOV AX, SEG ;  
MOV ES, AX ;  
MOV DI, OFFSET ;  
MOV CX,10 •  
MOV AX, WORD •  
CLD ; Clear DF  
REPNE SCASW •
```

- a) Differentiate between the following instructions. (4 marks)
- i. DIV and DIV
 - ii. MUL and IMUL
- b) Discuss the concept of interrupts in assembly language programming. How are they handled? (4 marks)
- c) Write a program to implement the JUMP instruction. (6 marks)

